SIEMENS

Data sheet

3VJ1103-5DB32-0AA0

circuit breaker 3VJ1 IEC framesize 3VJ11 125A line protection ATFM 3-pole Icu=36kA@415V Ics=75% Icu In=32A overload protection Ir=25.6A...32A short-circuit protection Ii=600A Screw connection

| Model | |
|---|-----------------------------------|
| product designation | Molded Case Circuit Breaker |
| design of the product | Line protection |
| design of the overcurrent release | ATFM |
| protection function of the overcurrent release | LI |
| number of poles | 3 |
| General technical data | |
| insulation voltage / rated value | 1 000 V |
| operating voltage / at AC / rated value | 415 V |
| power loss [W] / maximum | 31.5 W |
| power loss [W] / for rated value of the current / at AC / in hot operating state / per pole | 10.5 W |
| mechanical service life (operating cycles) / typical | 15 000 |
| electrical endurance (operating cycles) / at AC-1 / at 380/415 V | 5 000 |
| ground-fault monitoring version | without |
| Net Weight | 1.42 kg |
| Current | |
| continuous current / rated value | 32 A |
| operational current | |
| • at 40 °C | 32 A |
| • at 45 °C | 32 A |
| • at 50 °C | 32 A |
| • at 55 °C | 31.104 A |
| • at 60 °C | 30.208 A |
| Switching capacity according to IEC 60947 | 30.200 A |
| | |
| maximum short-circuit current breaking capacity (Icu) • at 415 V | 36 kA |
| | 30 KA |
| operating short-circuit current breaking capacity (lcs) | 27 kA |
| • at 415 V | ZT NA |
| short-circuit current making capacity (lcm) • at 415 V | 75.6 kA |
| | 75.0 KA |
| Adjustable parameters adjustable current response value current / of the current- | 25.6 32 A |
| dependent overload release | 20.0 027 |
| adjustable current response value current / of instantaneous short-circuit trip unit | |
| • minimum | 600 A |
| maximum | 600 A |
| product function / grounding protection | No |
| Mechanical Design | |
| height | 150 mm |
| width | 92 mm |
| depth | 85 mm |
| Connections | |
| arrangement of electrical connectors / for main current circuit | Front connection |
| type of electrical connection / for main current circuit | Lug connection line and load side |
| Accessories | |
| product extension / optional / motor drive | No |
| Environmental conditions | |
| protection class IP / on the front | IP42 |
| ambient temperature | |

-10 °C • during operation / minimum 60 °C • during operation / maximum • during storage / minimum -15 °C • during storage / maximum 75 °C

Approvals / Certificates

Test Certificates other

Type Test Certificates/Test Report

Confirmation

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VJ1103-5DB32-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3VJ1103-5DB32-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VJ1103-5DB32-0AA0


CAx-Online-Generator


http://www.siemens.com/cax


Tender specifications

http://www.siemens.com/specifications









3P Knob cutout

3P Nameplate cutout

last modified:

8/9/2023