SIEMENS

Data sheet

3VJ1106-5DB32-0AA0

circuit breaker 3VJ1 IEC framesize 3VJ11 125A line protection ATFM 3-pole lcu=36kA@415V lcs=75% lcu In=63A overload protection Ir=50.4A...63A short-circuit protection Ii=10 x In Screw connection

Model	Circuit protection in 10 x in outew connection
product designation	Molded Case Circuit Breaker
design of the product	Line protection
design of the overcurrent release	ATFM
protection function of the overcurrent release	LI
number of poles	3
General technical data	
insulation voltage / rated value	1 000 V
operating voltage / at AC / rated value	415 V
power loss [W] / maximum	31.5 W
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	10.5 W
mechanical service life (operating cycles) / typical	15 000
electrical endurance (operating cycles) / at AC-1 / at 380/415 V	5 000
ground-fault monitoring version	without
Net Weight	1.42 kg
Current	
continuous current / rated value	63 A
operational current	
• at 40 °C	63 A
• at 45 °C	63 A
• at 50 °C	63 A
• at 55 °C	61.236 A
• at 60 °C	59.472 A
Switching capacity according to IEC 60947	
maximum short-circuit current breaking capacity (Icu)	
• at 415 V	36 kA
operating short-circuit current breaking capacity (lcs)	
• at 415 V	27 kA
short-circuit current making capacity (Icm)	
• at 415 V	75.6 kA
Adjustable parameters	
adjustable current response value current / of the current- dependent overload release	50.4 63 A
adjustable current response value current / of instantaneous short-circuit trip unit	
• minimum	630 A
• maximum	630 A
product function / grounding protection	No
Mechanical Design	
height	150 mm
width	92 mm
depth	85 mm
Connections	
arrangement of electrical connectors / for main current circuit	Front connection
type of electrical connection / for main current circuit	Lug connection line and load side
Accessories	
product extension / optional / motor drive	No
Environmental conditions	
protection class IP / on the front	IP42
ambient temperature	11 74
ambient temperature	

-10 °C • during operation / minimum 60 °C • during operation / maximum • during storage / minimum -15 °C • during storage / maximum 75 °C

Approvals / Certificates

Test Certificates other

Type Test Certificates/Test Report

Confirmation

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

http://www.siemens.com/lowvoltage/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VJ1106-5DB32-0AA0

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3VJ1106-5DB32-0AA0

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VJ1106-5DB32-0AA0


CAx-Online-Generator


http://www.siemens.com/cax


Tender specifications

http://www.siemens.com/specifications









3P Nameplate cutout

last modified:

8/9/2023